

Product Specifications

FS1251



Fuel/Water Sep Spin-On

Fleetguard® FS1251 premium fuel water separator spin-on works to remove water and other particulates and ensures clean fuel is delivered to your engine.

View product on Fleetguard.com

Specifications

Tamaño de rosca	M16 X 1.5-6H INT	Longitud	5.63 inch
mayor diámetro exterior	3.02 inch	Diámetro Interior De La Junta	2.46 inch
Diámetro Exterior De La Junta Separación De Agua Emulsionada	2.72 inch 90%	Tubo Vertical	YES
		Especificación De Prueba	ISO TR13353
		Eficiencia De Partículas Primarias	17.3 micron (c) @ 96%
Ruptura Hidrostática Mínima	300.15 psi		

Related Parts

Replaces	FF5047	FS1226
Filter Used With	3311505S	
Upgrade Of	FF5052	
Is A Longer Version Of	FS1235	

Uses Service Gasket 3311919

"Fleetguard is a brand of Atmus Filtration Technologies ("Atmus"). This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to customers of Atmus Filtration Technologies Inc. and its subsidiaries (collectively, "Atmus") "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Atmus does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Atmus directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2025 Atmus Filtration Technologies Inc. All Rights Reserved