



Product Specifications

LF17559



Lube

Fleetguard® LF17559 spin-on lube filter meets or exceeds OE performance requirements and the new challenges of modern engine technology.

[View product on Fleetguard.com](https://www.fleetguard.com)

Specifications

Diámetro Exterior De La Junta	4.41 inch	Longitud	9.80 inch
mayor diámetro exterior	4.75 inch	A Frecuencia 2	ISO 4548-12
Válvula De Presión	No	Ruptura Hidrostática Mínima	246.49999999999997 psi
Eficiencia De Partículas Primarias	30 micron (c) @ 95%	Flujo Nominal	151.4 L/m
Diámetro Interior De La Junta	3.89 inch	Especificación De Prueba	ISO 4548-12
Tamaño de rosca	1 1/2-1.4642 UNF 2B		

"Fleetguard is a brand of Atmus Filtration Technologies ("Atmus"). This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to customers of Atmus Filtration Technologies Inc. and its subsidiaries (collectively, "Atmus") "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Atmus does not warrant the accuracy nor completeness of the Publication; may make changes

to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Atmus directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2025 Atmus Filtration Technologies Inc. All Rights Reserved