



Product Specifications

LF3536



Lube, Full-Flow Spin-On

Fleetguard® LF3536 spin-on lube filter meets or exceeds OE performance requirements and the new challenges of modern engine technology.

[View product on Fleetguard.com](https://www.fleetguard.com)

Specifications

| | | | |
|------------------------------------|-----------------------|-------------------------------|-------------|
| Tamaño de rosca | M20X15-6H | Diámetro Interior De La Junta | 2.26 inch |
| Diámetro Exterior De La Junta | 2.52 inch | Longitud | 4.02 inch |
| mayor diámetro exterior | 3.17 inch | A Frecuencia 2 | ISO 4548-12 |
| Eficiencia De Partículas Primarias | 24.6 micron (c) @ 95% | Tipo De Medio | Cellulose |

Product Comments

For Fluted shell version, see LF16157.

"Fleetguard is a brand of Atmus Filtration Technologies ("Atmus"). This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to customers of Atmus Filtration Technologies Inc. and its subsidiaries (collectively, "Atmus") "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Atmus does not warrant the accuracy nor completeness of the Publication; may make changes

to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Atmus directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2025 Atmus Filtration Technologies Inc. All Rights Reserved