



Product Specifications

LF3614



Lube, Spin-On

Fleetguard® LF3614 spin-on lube filter meets or exceeds OE performance requirements and the new challenges of modern engine technology.

[View product on Fleetguard.com](https://www.fleetguard.com)

Specifications

Longitud	2.90 inch	Diámetro Exterior De La Junta	2.48 inch
Ruptura Hidrostática Mínima	350.0129535 PSI	A Frecuencia 2	ISO 4548-12
Válvula De Presión	Yes	Tipo De Medio	Cellulose
Presión De Apertura De La Válvula De Presión	96.46 kPa	Eficiencia De Partículas Primarias	30 micron (c) @ 98.7%
Flujo Nominal	11.4 L/m	Diámetro Interior De La Junta	2.17 inch
mayor diámetro exterior	2.69 inch	Especificación De Prueba	ISO 4548-12
Tamaño de rosca	3/4-16 UNF 2B		

"Fleetguard is a brand of Atmus Filtration Technologies ("Atmus"). This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to customers of Atmus Filtration Technologies Inc. and its subsidiaries (collectively, "Atmus") "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property.

Atmus does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Atmus directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2025 Atmus Filtration Technologies Inc. All Rights Reserved