

Product Specifications

FF5011



Fuel, Spin-On

Fleetguard® FF5011 spin-on fuel filter delivers superior performance using proven media technology, removing harmful contaminants. Fleetguard fuel filters ensure optimal fuel system protection to meet or exceed OEM specifications.

View product on Fleetguard.com

Specifications

Tamaño de rosca	1-12 UNF-2B	Diámetro Interior De La Junta	2.46 inch
Diámetro Exterior De La Junta	2.83 inch	Longitud	7.70 inch
mayor diámetro exterior	3.69 inch	Tubo Vertical	No
A Frecuencia 2	SAE J905	Ruptura Hidrostática Mínima	203.0 psi
Eficiencia De Partículas Primarias	17.3 micron (c) @ 97%	Flujo Nominal	7.58 L/min
Fillialias	₩ 91 /o	i iujo ivoiminai	7.30 L/IIIII
Tipo De Medio	Cellulose		

Product Comments

Farm fuel tanks. Service pumps w/drain cock. Diesel fuel only. Older version has Drain Valve, newer version has a Drain Plug.

"Fleetguard is a brand of Atmus Filtration Technologies ("Atmus"). This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to customers of Atmus Filtration Technologies Inc. and its subsidiaries (collectively, "Atmus") "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Atmus does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Atmus directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2025 Atmus Filtration Technologies Inc. All Rights Reserved