



Product Specifications

FF5785



Fuel, Spin-On

Fleetguard® FF5785 spin-on fuel filter delivers superior performance using proven media technology, removing harmful contaminants. Fleetguard fuel filters ensure optimal fuel system protection to meet or exceed OEM specifications.

[View product on Fleetguard.com](http://Fleetguard.com)

Specifications

A Frecuencia 2	ISO 19438	Ruptura Hidrostática Mínima	434.99999999999994 psi
Flujo Nominal	4 L/min	mayor diámetro exterior	3.70 inch
Longitud	5.61 in	Diámetro Exterior De La Junta	2.76 inch
Diámetro Interior De La Junta	2.44 inch	Tamaño de rosca	M18X1.5-6H

This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Cummins Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Cummins Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products,

programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2025 Cummins Filtration Inc. All Rights Reserved