



Product Specifications

LF16006



Lube

Fleetguard® LF16006 spin-on lube filter meets or exceeds OE performance requirements and the new challenges of modern engine technology.

[View product on Fleetguard.com](https://www.fleetguard.com)

Specifications

Tamaño de rosca	1-16 UNF 2B	Longitud	6.94 inch
mayor diámetro exterior	3.68 inch	Diámetro Interior De La Junta	2.46 inch
Diámetro Exterior De La Junta	2.83 inch	A Frecuencia 2	SAE J1858
Válvula De Presión	No	Ruptura Hidrostática Mínima	203.0 psi
Eficiencia De Partículas Primarias	24.6 micron (c) @ 100%	Flujo Nominal	33 L/m
Especificación De Prueba	SAE J1858		

Product Comments

Used on 6B engines, Remote Mount Unit

"Fleetguard is a brand of Atmus Filtration Technologies ("Atmus"). This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a

convenience to customers of Atmus Filtration Technologies Inc. and its subsidiaries (collectively, "Atmus") "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Atmus does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Atmus directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2025 Atmus Filtration Technologies Inc. All Rights Reserved