



Product Specifications

LF17502



Lube, By-Pass Spin-On

Fleetguard® LF17502 premium spin-on lube filter meets or exceeds OE performance requirements and the new challenges of modern engine technology.

[View product on Fleetguard.com](https://www.fleetguard.com)

Specifications

Diámetro Exterior De La Junta	4.02 inch	Longitud	10.24 inch
mayor diámetro exterior	4.31 inch	A Frecuencia 2	ISO 4548-12
Válvula De Presión	No	Tipo De Medio	Cellulose
Ruptura Hidrostática Mínima	246.49999999999997 psi	Eficiencia De Partículas Primarias	16 micron (c) @ 98.7%
Flujo Nominal	10.8 L/m	Diámetro Interior De La Junta	3.70 inch
Especificación De Prueba	ISO 4548-12	Tamaño de rosca	1 3/8-16 UNF 2B

Product Comments

Compatible with Euro 6 oils

Related Parts

Upgrade Of	LF3654
Is European Version Of	LF3654

This publication and all information contained or referenced in it (hereinafter "Publication") are provided asa convenience to Cummins Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property.Cummins Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2025 Cummins Filtration Inc. All Rights Reserved