



Product Specifications

LF3310



Lube, Spin-On

Fleetguard® LF3310 spin-on lube filter meets or exceeds OE performance requirements and the new challenges of modern engine technology.

[View product on Fleetguard.com](https://www.fleetguard.com)

Specifications

Tamaño de rosca	3/4-16 UNF 2A	Diámetro Exterior De La Junta	2.83 inch
Diámetro Interior De La Junta	2.46 inch	mayor diámetro exterior	2.99 inch
Longitud	3.49 inch	A Frecuencia 2	SAE J1858
Válvula De Presión	No	Presión De Apertura De La Válvula De Presión	206.8 kPa
Eficiencia De Partículas Primarias	48 micron (c) @ 98.7%		

Related Parts

Is Metal Version Of LF42500

"Fleetguard is a brand of Atmus Filtration Technologies ("Atmus"). This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to customers of Atmus Filtration Technologies Inc. and its subsidiaries (collectively, "Atmus") "as is" without any warranties, express or implied, including warranties of

merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Atmus does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Atmus directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2025 Atmus Filtration Technologies Inc. All Rights Reserved