



# Product Specifications

## LF3311



### Lube, Full-Flow Spin-On

Fleetguard® LF3311 spin-on lube filter meets or exceeds OE performance requirements and the new challenges of modern engine technology.

[View product on Fleetguard.com](#)

## Specifications

Tamaño de rosca	3/4-16 UNF 2B	Diámetro Interior De La Junta	2.46 inch
Diámetro Exterior De La Junta	2.83 inch	mayor diámetro exterior	3.79 inch
Longitud	3.75 inch	Válvula De Presión	Yes
Ruptura Hidrostática Mínima	203.0 psi	Flujo Nominal	20 L/m
Eficiencia De Partículas Primarias	24.6 micron (c) @ 95%		

## Related Parts

**Replaces**      HF7931

This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Cummins Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or

non-infringement of intellectual property. Cummins Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2025 Cummins Filtration Inc. All Rights Reserved