



Product Specifications

LF3830



Lube, Full-Flow Spin-On

Fleetguard® LF3830 spin-on lube filter meets or exceeds OE performance requirements and the new challenges of modern engine technology.

[View product on Fleetguard.com](#)

Specifications

Diámetro Exterior De La Junta	2.83 inch	mayor diámetro exterior	4.28 inch
Longitud	5.92 inch	Válvula De Presión	Yes
Tipo De Medio	Cellulose	Ruptura Hidrostática Mínima	255.95399999999998 psi
Presión De Apertura De La Válvula De Presión	110.31 kPa	Eficiencia De Partículas Primarias	30.5 micron (c) @ 98.7%
Flujo Nominal	22.7 L/m	Diámetro Interior De La Junta	2.46 inch
Tamaño de rosca	M26X1.5-6H		

"Fleetguard is a brand of Atmus Filtration Technologies ("Atmus"). This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to customers of Atmus Filtration Technologies Inc. and its subsidiaries (collectively, "Atmus") "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Atmus does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Atmus directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2025 Atmus Filtration Technologies Inc. All Rights Reserved